

EASY GO

Lazer markalama sistemi
Marking laser system



EASY GO OPEN

Lazer markalama sistemi
Marking laser system



Teknik Veri	Technical Data	200F	300F
Ortalama güç	Average power	20 W	30 W
Dalgaboyu	Wavelength	1060 nm - 1085 nm	1060 nm - 1085 nm
Tek darbe enerjisi	Single pulse energy	1 mJ @20 kHz	1 mJ @20 kHz
Darbe süresi	Pulse duration	120 ns @20 kHz	120 ns @20 kHz
Işın kalitesi	Beam quality	<1.8 M2	<1.8 M2
Red pointer	Red pointer	Class 2M diode red; λ=650 nm; 2 mW	Class 2M diode red; λ=650 nm; 2 mW
Çalışma sıcaklığı	Working temperature	10°C - 35°C	10°C - 35°C
Soğutma sistemi	Cooling system	Forced air / Basınçlı Hava	Forced air / Basınçlı hava
Z eksen hareketi	Z axis stroke	340 mm	340 mm
4. eksen	4th axes	Optional/Opsiyonel	Optional/Opsiyonel
Güç kaynağı	Power supply	230 V ± 15% 50/60 Hz 1ph CEE 16 plug	230 V ± 15% 50/60 Hz 1ph CEE 16 plug
Boyutlar	Dimensions [WxDxH]	555 mm x 685 mm x 795 mm	555 mm x 685 mm x 795 mm
Ağırlık	Weight	110 kg	110 kg

LOGO

Lazer markalama
Marking laser

Teknik Veri	Technical Data
Dalgaboyu	Wavelength 1064 nm
Maks. güç	Peak Power 20 KW
Darbe süresi	Pulse Duration 4 ns
Working table dimension [L x l x h]	mm 200x160x180 with lens 100 mm
Çalışma tablosu boyutları [L x l x h]	mm 200x160x105 with lens 160 mm
"Z" eksen	"Z" axis Manual • Manuel
Frekans	Frequency Fixed • Sabit
Odak kiti	Focus Kit Included • Dahil
Boyutlar	Dimensions [W x D x H] 481 x 446 x 604 mm
Ağırlık	Weight 35 Kg

